

USPTO PATENT FULL-TEXT AND IMAGE DATABASE

[Home](#)[Quick](#)[Advanced](#)[Pat Num](#)[Help](#)[Next List](#)[Bottom](#)[View Cart](#)

Searching US Patent Collection...

Results of Search in US Patent Collection db for:
(ACLM/decibel OR ACLM/decibels): 915 patents.
Hits 1 through 50 out of 915

[Next 50 Hits](#)[Jump To](#)[Refine Search](#)

aclm/decibel or acalm/decibels

PAT. NO.	Title
-------------	-------

- | | | |
|----|---------------------------|---|
| 1 | 7,272,473 | T Methods and systems for analyzing system operator coupling susceptibility |
| 2 | 7,272,178 | T Method and apparatus for controlling the bandwidth frequency of an analog filter |
| 3 | 7,269,190 | T Er-doped superfluorescent fiber source with enhanced mean wavelength stability |
| 4 | 7,266,103 | T Controlling forward link traffic channel power |
| 5 | 7,265,620 | T Wide-band high-gain limiting amplifier with parallel resistor-transistor source loads |
| 6 | 7,262,903 | T Method and apparatus for controlling multiple-wavelength-pumped raman amplifier and computer product |
| 7 | 7,260,364 | T Reverse mounted micro-speaker assemblies and mobile terminals including the same |
| 8 | 7,259,906 | T System and method for voice control of medical devices |
| 9 | 7,259,779 | T Automatic assessment of de-interlaced video quality |
| 10 | 7,258,630 | T Multiple material golf club head |
| 11 | 7,258,287 | T Modular fuel injector with a spiral damper member and method of reducing noise |
| 12 | 7,256,564 | T System and method for attenuating noise associated with a back electromotive force signal in a motor |
| 13 | 7,254,337 | T Band optical add/drop multiplexing |
| 14 | 7,253,700 | T Circuit for controlling a linear-in-decibels attenuator circuit using an analog control signal |
| 15 | 7,248,706 | T Audio-signal detecting device |
| 16 | 7,233,432 | T Pre-emphasized optical communication |
| 17 | 7,233,298 | T High performance antenna |
| 18 | 7,226,955 | T Macrocellular acoustic foam containing particulate additive |
| 19 | 7,224,513 | T Pumping light source having amplification-band extending function for Raman amplification, Raman amplifier using the same, and method and program for setting amplification band extension |
| 20 | 7,221,755 | T Method of capturing constant echo path information in a full duplex speakerphone |
| 21 | 7,221,714 | T Non-systematic and non-linear PC-TCM (Parallel Concatenate Trellis Coded Modulation) |
| 22 | 7,221,552 | T Wearable shield and self-defense device |
| 23 | 7,202,731 | T Variable distortion limiter using clip detect predictor |
| 24 | 7,199,720 | T Hearing protection warning device |

- 25 7,197,245 **T** System and method for managing system margin
- 26 7,196,655 **T** System and method for highly directional electronic identification and communication and combat identification system employing the same
- 27 7,196,583 **T** Power control of a power amplifier
- 28 7,193,567 **T** TM microstrip antenna with GPS frequency coverage
- 29 7,190,966 **T** Method and apparatus for performing an access procedure
- 30 7,190,583 **T** Self contained, liquid to air cooled, memory test engineering workstation
- 31 7,190,548 **T** Encapsulated miniature hard disc drive
- 32 7,187,915 **T** Automatic gain control for a WLAN system
- 33 7,187,829 **T** Low smoke, low toxicity fiber optic cable
- 34 7,187,280 **T** Alarm system with thin profile
- 35 7,185,270 **T** LDPC (low density parity check) coded modulation hybrid decoding
- 36 7,184,489 **T** Optimization technique for layered modulation
- 37 7,183,771 **T** Multiple transmitter and receiver well logging device with error calibration system including calibration injection system
- 38 7,180,997 **T** Method and system for improving the intelligibility of a moderator during a multiparty communication session
- 39 7,170,345 **T** Predistorter
- 40 7,167,525 **T** Ultra-wideband communication through twisted-pair wire media
- 41 7,162,475 **T** Method for user verification and authentication and multimedia processing for interactive database management and method for viewing the multimedia
- 42 7,162,204 **T** Configurable spectral mask for use in a high data throughput wireless communication
- 43 7,157,890 **T** Using pulse width modulation in the control of load sharing between paralleled power supplies
- 44 7,154,200 **T** Motor
- 45 7,145,966 **T** Signal quality estimation for continuous phase modulation
- 46 7,142,144 **T** Low power sigma delta modulator
- 47 7,139,330 **T** System for signal mixing and method thereof
- 48 7,136,418 **T** Scalable and perceptually ranked signal coding and decoding
- 49 7,135,643 **T** EMI shield including a lossy medium
- 50 7,132,977 **T** Target identification from a pool of targets using a new adaptive transmitter-receiver design
-

